

MINISTICK DELUXE





Properties

- Operates with 1 Phase 230V-50/60 Hz mains voltage and generators, tolerates voltage fluctuations up to 15%.
- Due to inverter technology, energy efficiency is higher than the conventional machines.
- Excellent welding characteristics for rutile and basic electrodes up to 3.25 mm in diameter.
- Current adjustment scale by electrode diameters for easy parameter selection.
- Scratch TIG welding on even thin metals due to its stable low currents.
- The smallest model of the family with a weight of 4 kg and the compact design, it can easily be carried or hanged by the shoulder strap.
- Stable welding current without loss of performance due to electric line fluctuations or with longer welding and electrical cables.
- Designed also for outdoor use, protection class is IP 23.
- Fan cooling and thermal protection against overheating.
- Standard accessories come with the machine.

Technical Specifications

Power Source		
Mains Voltage (1Ph)	230	V
Input Power	6.83	kVA
Welding Current Range	5 - 140	A
Devrede Kalma Oranı (@25°C)	130	A (%100)
EN 60974 -1 (I/X%)	140/15	
Devrede Kalma Oranı (@25°C)	140	A (%70)
Open Circuit Voltage	75 VDC	V
Electrode Diameter	1.60 - 3.25	mm
Dimensions (l x w x h)	360 x 120 x 200	mm
Weight (Net)	4.25	Kg
Protection Class	IP 23	

Standard Accessories

Accessories Picture	Code	Name	
	7906101602	Electrode Clamp And Cable	Standard
	7905101602	Ground Clamp And Cable	Standard

Opsiyonel Aksesuarlar

Accessories Picture	Code	Name	
	7111014004	LAVA TIG 17V-4 VALVE	Optional