

WhaleSpray

Technical Data Sheet



WS 1803 G

Range: Welding
Product code: 1803G00

Creation date: 02/11/2016
Review date: 16/09/2016
Page: 1/1

Description

Prevention and elimination of welding spatters water-based. WS 1803 G provides a quick and easy way to prevent the adhesion of projections on metal surfaces during welding, and eliminates the need for chiseling, sharpening or brushing with wire brush after welding. Prevents clogging of automatic and semi-automatic welding equipment nozzles.

Properties

- Extends the life of the nozzles.
- Increases the stability of the arch, ensuring the free flow of gas.
- Silicone free heat resistant barrier.
- Long-lasting non-stick effect.
- The welding projections are easily removed by brushing.
- Saves time and money.
- Free of solvents without risk in the work environment.
- Absolute compatibility with paints, glues, adhesives and varnishes.
- Does not produce fumes or odors in welding processes.
- It is not necessary to degrease the piece before painting.

How to use

- Shake before using
- Apply a thin film on the surface to be welded.
- Spray inside the nozzle before starting.
- The projections can be cleaned with a cloth or by gently "tapping" the nozzle on one side of the bench.
- Provide normal ventilation while welding.

Technical information

	Limit values	Typical values
Appearance	Foaming liquid without color	-
Specific weight @ 20°C		1,002
Flash point		None
pH		9,5
Typical thickness of the film		2-5 microns



WhaleSpray
Spray everything

www.whalespray.com
P.I. Ametlla Park · c/ Aiguafreda, 24
08480 L'Ametlla del Vallès · Barcelona
Tel. 900 15 20 40 · Fax 902 15 20 45

Síguenos en:
 ISO 9001-ISO 14001
Empresa Certificada ISO 9001-ISO 14001
Company certified ISO 9001-ISO 14001